
EMO
ENVIRONMENT BY TECHNOLOGY

SCV

Screw conveyor

Screw conveyors manufactured by EMO are designed for the transport of waste from screening and urban or industrial thickened sludge.

They can be easily adapted to your existing constraints and are available in an infinite number of versions: horizontal, inclined or rotating screw. They are designed to ensure the recovery, transfer or distribution of your dewatered sludge in dumps after treatment.



ADVANTAGES

- Optimum and safe use
- Equipped with a cover mounted on a slide
- Inclinaison jusqu'à 30°
- Length on request : no limit !

EMOPRD00750-DPR00-A-EN







Information: the technical data announced are not contractual and may change at any time.


OPERATING PRINCIPLE

The screw conveyor consists in a shaftless and endless screw rotating in a «U» shape trough, lined with a durable material.The screw is driven by a single speed gearmotor..

The products to be transported (screenings, thickened sludge) fall into a feed hopper, fixed to the upper part of the conveyor. They are then pushed from one point to another by the force exerted by a shaftless and endless screw itself driven by a gearmotor.

The absence of a shaft and of intermediate brackets has the effect of eliminating almost completely any risk of clogging during the transport of wet, sticky or fibrous materials.


1



Shaftless screw


Simple or double spiral for evacuation of sludge from plate filter press.

2



Feed hopper

Modular: with grid, cover and opening sensor(s).



RANGE & APPLICATIONS

Capacity figures represent maximum recommended capacities in m³/h for a conveyor rotating at 35 rpm handling typical dewatered municipal sludge.
For screenings and similar difficult materials, typical speed is 15 rpm and capacities are reduced to 20% of those shown.

Description	
Type SCV	from 190 à 360
Screw diameter *	from 190 mm to 360 mm
Inclination angle	from 0° to 30°
Capacity for conveying	from 1,2 to 20 m³/h

* larger diameter(s) upon request



EMO sas,
4 rue Lépine – PA La Richardière, BP 53209, 35530 Noyal sur Vilaine, France
+ 33 (0)2 99 86 02 03 - emo@emo-france.com
www.emo-france.com
Certification ISO9001 - ISO14001

FABRIQUÉ EN FRANCE · MADE IN FRANCE

A company SEMOSIA GROUP